

Scout Liner Top Packer

The Scout Liner Top Packer is a premium packer specifically designed for the harshest of environments. The packer offers both a high-torque running profile for both hydraulic and mechanical running tools.

Tie Back receptacles are available in a variety of lengths to accommodate all well-bore environments. Integral hold-down slips lock the packer into the casing wall to prevent upward movement.

The packer is ideal for reaming operations and rotating while cementing. The element is V0 rated to 10,000 psi and V3 rated to 12,500 psi.

FEATURES AND BENEFITS

- ISO V0 qualified: 10,000 psi, 350°F, Aflas element
- ISO V3 qualified: 12,500 psi, 350°F, HNBR element
- High-torque rating for drill-in and reaming applications
- Low-profile design for improved bypass area
- Integral anti back-off feature for tieback sleeve
- Allows for tieback extensions of nearly any length, with 15 ft and 20 ft as standards
- Integral hold-down slip system
- Enhanced extrudable element provides higher sealing capability for damaged or non-concentric casing
- Premium thread standard



SCOUT LINER TOP PACKER

SIZE Inches	CASING WEIGHT	TOOL O.D. Inches	TOOL I.D. Inches
5.000x7.000	7.000" 26-29 PPF	5.919	4.293
5.000x7.000	7.000" 26-35 PPF	5.849	4.293
7.000x9.625	9.625" 36-47 PPF	8.472	6.164
7.000x9.625	9.625" 43.5-53.5 PPF	8.329	6.164